CALENN TRILLIPS

Glen- To be published this spring in Vol 9, Issue #2 of NAJEM

A NEW TECHNIQUE FOR MEASURING FINE SEDIMENT IN STREAMS

bv

Thomas A. Wesche
Wyoming Water Research Center
University of Wyoming
Laramie, Wyoming 82071, U.S.A.

Dudley W. Reiser

EA Engineering, Science and Technology, Inc.
Lafayette, California 94549, U.S.A.

Victor R. Hasfurther Department of Civil Engineering University of Wyoming

Wayne A. Hubert
U.S. Fish and Wildlife Service
Wyoming Cooperative Fishery and
Wildlife Research Unit
Department of Zoology and Physiology
University of Wyoming

and

Quentin D. Skinner
Department of Range Management
University of Wyoming

Abstract. Techniques commonly used to measure fine sediment accumulation in streambed gravels can be labor and equipment intensive. We evaluated the sediment trapping capabilities of modified Whitlock-Vibert boxes under both laboratory and field conditions, and compared the accumulated fine sediment to that contained in adjacent gravels as indicated by McNeil core samples. Our results suggest the boxes can be used as an alternative to core sampling for monitoring intergravel fine sediment levels. Advantages include ease of transport to remote field sites, small sample volumes, and reduced analysis time. Problems encountered were displacement by flood and ice flows and inundation by large sediment spills.

The effects of fine sediment on stream biota and their habitat include: 1) reduction of primary production, (2) damage to respiratory organs, (3) encombment of organisms, (4) increased disease, (5) reduction of rearing and spawning habitat, (6) reduction of intragravel dissolved oxygen and flow, and (7) alteration of water chemistry (Cordone and Kelley, 1961; Cibbons and Salo, 1973; Iwamoto et al., 1978). While research has focused on describing the effects of sediment deposition, less effort has been directed toward the development of methods for measuring the accumulation of fine sediment in streambeds. Two types of samplers are commonly used for characterizing substrate composition -- the McNeil core sampler and the freeze-core sampler (Platts et al., 1983, Reiser et al., 1985). The major deficiency of the McNeil sampler is the the inability to insert the sampler to the specified depth, if the substrate is coarse or compacted. The major disadvantage of the freeze-core technique is that the large, bulky equipment limits sampling to readily accessible areas. Also, freeze-core probes can be difficult to drive through large substrates and the weight of samples can make handling difficult. Shortcomings of core sampling and freeze-core techniques have resulted in efforts to develop sediment "trapping" devices (Meehan and Swanston, 1977; Mahoney and Erman, 1984).

The objective of this study was to test the hypothesis of Reiser and White (1981) that a correlation exists between the percentage of fine sediments trapped by Whitlock-Vibert boxes and that contained in McNeil core samples. We conducted experiments in an artificial flume at different flows and in channel sections with different gradients to test the hypothesis.

Methods

Whitlock-Vibert (W-V) boxes are made of polypropylene and measure 14 x 6.4 x 8.9 cm deep. The sides, top and bottom of the boxes are perforated with rectangular slots to allow water circulation. Openings in the top and the largest slots on the sides are 3.5 mm x 13 mm. We removed the inner panel from the W-V boxes to increase their effectiveness as sediment traps. The boxes were filled with clean gravel 12-25 mm in diameter (Figure 1) and a strip of duct tape was placed on the bottom of each box to prevent the loss of trapped fine sediment through the bottom.

Initial testing of the sediment-trapping capabilities of the modified W-V boxes was conducted in an experimental flume (Hydraulics Laboratory, University of Wyoming). The concrete flume was 21.3 x 0.9 x 0.9 m deep and filled to a depth of 0.46 m with bed material (including fines) similar in composition to that used by salmonids for spawning in southeast Wyoming (Reiser and Wesche, 1977). The substrate was formed into three riffle-pool sequences. Discharge through the channel was controlled by a series of five recirculating pumps.

Three experiments were conducted during 1984 and 1985 with each following the same general procedure. Modified W-V boxes were planted in each riffle and pool. Pumps were activated and flow was varied throughout the experiment (maximum 0.14 m³/s). Suspended sediment samples and bedload samples were taken at the head of each riffle to determine sediment movement. At the conclusion of each experiment, W-V boxes were carefully removed from the substrate, placed in plastic bags, and stored until analysis. At a location immediately adjacent to each

W-V box, a McNeil core sample was collected. All samples were dried at 70°C for at least 24 hours and gravimetrically analyzed by the dry sieve technique, with results reported as percent of total dry sample weight. Fines of three sizes were measured: < 3.35, < 1.75, and < 0.85 mm diameter.

Among the three experiments several conditions varied. Experiment 1 lasted 3 days, peak discharge was $0.08 \text{ m}^3/\text{s}$, and 44 W-V boxes were planted 7.6 cm deep in the substrate. Experiment 2 ran for 5 days, peak discharge was $0.12 \text{ m}^3/\text{s}$, and 46 boxes were planted with their tops flush with the surface of the substrate. Experiment 3 was similar to 2 with the exceptions that 92 boxes were planted and 1,818 kg of fine sediment (<3.35 mm diameter) were continuously added to the system at the upper end of the flume.

Correlation analysis was used to determine relations between the percentage of fine sediment trapped in the W-V boxes and that present in adjacent McNeil core samples. To test the efficiency of the two methods, we compared the percentage of fine sediment using pared t-tests. For each experiment, separate statistical analyses were conducted for all samples combined, all riffle samples, all pool samples, and all samples taken from mid-channel.

Field testing was conducted during 1985 on the North Fork of the Little Snake River. Our purpose was to compare the percentage of fine sediment trapped by the W-V boxes to that contained in McNeil core samples and to evaluate the durability of the boxes over a wide range of field conditions. The North Fork of the Little Snake River is a steep

gradient stream located in the upper Colorado River basin of south-central Wyoming. Construction in the watershed contributed large amounts of sediment to the channel during 1984. Modified W-V boxes were planted in four reaches of the stream in 1985. Reach 1, the control section, had a moderate gradient (2.6%); it was located immediately upstream from construction activity, while Reaches 2, 3 and 4 were downstream of the construction and subject to sedimentation. Reach 2 was high gradient (4.5%), Reach 3 (3.0% slope) was most similar to the upstream control, and Reach 4 was low gradient (0.4%). Each reach was 12 m in length and averaged 6.5 m in width. Discharge varied from 0.1 to 3.1 m³/s.

Twelve modified W-V boxes were planted and recovered three times in each study reach. At each recovery time, McNeil core samples were taken at each reach. Study periods were: Test 1, October 1984-May 1985; Test 2, May 1985-July 1985; Test 3, July 1985-September 1985. All W-V boxes were planted with the top flush to the streambed surface. Sample handling in the field and laboratory analysis were the same as described for the laboratory experiments. Analysis-of-variance was used to compare fine sediment content of the boxes and the cores.

Results

In Experiment 1, the mean percentage of fines less than 3.35 mm diameter was significantly different ($\underline{P} \leq 0.05$) between W-V boxes and McNeil samples in all sample groupings (Table 1). Results were similar for fines less than 1.7 mm and 0.85 mm diameter. In all cases, the quantity of fines trapped by the modified W-V boxes was less than that

contained in the McNeil samples. Little fine bed material was transported during Experiment 1 (4 g/minute). The lack of bed material movement combined with the depth at which the boxes were planted limited the ability of W-V boxes to trap fines. Correlation coefficients were significant among all samples, riffle samples and mid-channel samples indicating a relation between the percentage of fines trapped by the W-V boxes and that in adjacent McNeil samples.

Results of Experiment 2 indicated the modified W-V boxes to be as effective a measure of fine sediment as McNeil core samples. Sediment transport during this experiment was 23 g/minute. No significant differences were observed between the mean percentage of fines less than 3.35 mm diameter and all correlation coefficients were significant. Similar results were obtained when fines less than 1.75 and 0.85 mm diameter were considered.

In Experiment 3, when fine sediment was added and sediment transport was 300 g/minute, the effectiveness of W-V boxes as a method to sample fine sediment was again shown. No significant differences were found between means with the exception of the pool sample. The discrepancy found in the pool data resulted from the filling of the upper two pools with large amounts of fine material. When McNeil samples were taken in these pools, the length of the sampling tube was not sufficient in many cases to penetrate through the fill layer (up to 15 cm of pure fines above the gravel substrate). Thus, the percent of fine material in the samples was abnormally high in comparison to the W-V boxes, which had coarse material placed in them prior to the initiation of the experiment. In the upper two pools, the mean

percentage of fines was significantly different ($\underline{P} \leq 0.05$) in the W-V boxes and the McNeil samples. In the lowest pool, however, where filling was not as severe, there was no significant difference.

The results of field testing (Table 2) were similar to those found under laboratory conditions. At Reaches 1, 2 and 3 (moderate to steep gradient) there was no significant differences ($\underline{P} \leq 0.05$) between the mean percentage of fine sediment in the W-V boxes and the McNeil samples. This relationship held for all three size categories of sediment.

The results from Reach 4, the low gradient pool, were similar to those from the upper two pool samples of laboratory Experiment 3.

During spring runoff in early May 1985, large quantities of fine sediment were moved into Reach 4. Deposition depth of this sediment ranged up to 30 cm throughout the pool. The significant differences found are most likely the result of this heavy deposition coupled with the size limitations of the slots of the W-V boxes. Despite the Reach 4 results, no significant differences were found for the mean percentage of fine sediment less than 0.85 mm when samples from all reaches were combined.

The durability of the W-V boxes throughout field testing was exceptional. More than 90% of the boxes could be reused at least three times, with most breakage resulting from handling during sub-freezing temperatures. A problem encountered was the displacement of planted boxes. Of 144 boxes planted during the 1985 field testing, 25 (17%) were flushed from the stream bottom and lost. Spring ice-out (12 boxes lost) and high streamflows (13 boxes lost) were the main causes of

displacement. Sixty percent of the losses occurred in Reach 2, the steep gradient site.

Discussion

Our results suggest that W-V boxes, planted flush with the streambed surface to enable bedload sediment to intrude into the boxes, can be used in place of McNeil samples to monitor fine sediment accumulation. The boxes' small size and low cost make them well suited for field use. In addition, field sampling is easier with W-V boxes than with McNeil or freeze core methods. For example, using our data from laboratory Experiment 2 pool samples, 164 modified W-V box samples or 161 McNeil core samples would be needed to be 95% confident that the sample mean was within 10% of the true mean (Burns, 1966). An average McNeil sample weighs 4.75 kg while an average W-V box sample weighs 1.0 kg, so total weight of the needed McNeil samples would be 765 kg while that of W-V box samples would be 164 kg material.

All of our W-V box samples were analyzed by the dry-sieve process. For many studies such detail may not be necessary. A quick, yet reliable, measure could be obtained by simply weighing the contents of the W-V boxes before planting and after recovery.

A problem encountered during both the laboratory experiments and the field testing was the inability of the boxes to sample high quantities of deposition above the gravel substrate. An alternative would be to measure the depth of sediment deposited over the top of the box. Knowing the surface area of the box top and this depth, the volume of sediment above the gravel substrate could be estimated, although not

all of this material may actually be fine sediment less than 3.35 mm diameter.

A second problem encountered during field testing was loss of W-V boxes due to displacement. During our experiments, no method of mechanically anchoring the boxes was attempted. Should sampling be necessary in steep gradient reaches during times when degradation of the streambed may occur (e.g., ice-out, spring runoff), boxes should be anchored into the streambed.

Acknowledgements

Support for this research project was provided by the State of Wyoming through the Wyoming Water Research Center, University of Wyoming.

References

- Burns, J.W. 1966. How big a sample. Pages 161-162 in A. Calhoun, editor Inland fisheries management. California Department of Fish and Game, Sacramento.
- Cordone, A.J. and D.W. Kelley. 1961. The influences of inorganic sediment on the aquatic life of streams. California Fish and Game 47:189-228.
- Gibbons, D.R. and E.O. Salo. 1973. An annotated bibliography of the effects of logging on fish of the western United States and Canada.

 U.S. Forest Service, General Technical Report, PNW-10.

- Iwamoto, R.N., E.O. Salo, M.A. Madej and R.L. McComas. 1978. Sediment and water quality: A review of the literature including a suggested approach for water quality criteria. U.S. Environmental Protection Agency, EPA-916/9-78-048, Seattle, Washington.
- Mahoney, D. and D.C. Erman. 1984. An index of stored fine sediment in gravel bedded streams. Water Resources Bulletin 20: 343-348.
- Meehan, W.R. and D.N. Swanston. 1977. Effects of gravel morphology on fine sediment accumulation and survival of incubating salmon eggs.

 U.S. Forest Service, Research Paper PNW-220.
- Platts, W.S., W.F. Megahan and G.W. Minshall. 1983. Methods for evaluating stream, riparian, and biotic conditions. U.S. Forest Service, General Technical Report INT-138.
- Reiser, D.W. and T.A. Wesche. 1977. Determination of physical and hydraulic references of brown and brook trout in the selection of spawning locations. Water Resources Series #64. University of Wyoming, Water Resources Research Institute, Laramie.
- Reiser, D.W. and R.G. White. 1981. Influence of streamflow reductions on salmonid embryo development and fry quality. Report Number A-058-IDA. University of Idaho Water and Energy Resources Research Institute, Moscow.
- Reiser, D.W., M.P. Ramey and T. Lambert. 1985. Review of flushing flow requirements. In: Regulated Streams. Pacific Gas and Electric Company, San Ramon, California.

Figure 1. Whitlock-Vibert boxes modified for sediment trapping.

Table 2. Comparison of mean percent fine sediment in modified W-V boxes and McNeil samples from North Fork Little Snake River study reaches, 1985.

THE ANALYSIS OF THE PROPERTY O	Sample size	SIZO	Tipes A	. 35 mm	Fines < 1.75 mm	3	Tines A	0.85 mm
Sample	XOG A-M	NCNe.11	W-V box McNeil	McNeil	W-V box	McNeil	W-V box McNei	McNe 11
Weach I	U	Ö.	22.8	29.6 ^a	16.7	μωί Φ μωί μωί Ω	10.2	5
Reach 2	2	26	22.4	22. Ja	5	U Va	9,2	7.5
Reach 3	32	36	25.1	30.4ª	16.9	19.62	9.4	5a
Reach 4	just	8	2	\$7.3	22.2	40.0	}	∾ •
Samples	119	144 444	24.0	Н •	grand and a	r L	10.0	12.0ª

a No significant difference between means at $\rho \leq 0.05$.

Table I. Comparison of mean percent fine sediment (< 3.35 mm diameter) in modified W-V boxes and McNeil samples, laboratory experiments 1, 2 and 3. Coefficient of variation in parentheses.

Experiment	Sample	Sample size	W-V boxes Mean fines (%)	McNell	
justi	Description of the control of the co	44	12.2 (41.8)	18.4 (36.7)	9.53
	70 Fr Fr Fr	22	14.0 (41.2)	21.8 (25.6)	0,490
	Pool	22	10.4 (35.3)	15.0 (41.2)	0.39
	Mid-channel	proce On	13.2 (46.2)	19.6 (38.4)	2 2
?	Demail jumps	46 a	11.4 (77.2)	13.7 (52.4)	9, 540
	Pi Pi Pi Pi	N 0	12.8 (84.5)	14.6 (44.1)	0
	Pool	23 a	10.0 (61.4)	12.9 (61.6)	0.596
	Mid-channel	a a	10.8 (72.8)	12.2 (60.0)	0.596
) 	926	31.0 (39.5)	37.3 (85.0)	0.396
	Police in the second se	465	33.5 (34.0)	27.9 (62.0)	o. 5,
4	Pool	46	28.5 (44.5)	46.5 (81.5)	٥ ٧,
	Mid-channe 1	28 ^a	32.7 (35.5)	39.2 (76.0)	0.20

^aNo significant difference between means at $\rho \leq 0.05$.

 $^{^{}m b}$ No significant difference between means at ho \leq 0.01.

 $^{^{\}rm c}$ r significant at $\rho \leq 0.05$.